

**BSPT Konisches Whitworth-Rohrgewinde DIN EN 10226-1/  
DIN EN 10226-2/ISO 7-1, früher DIN 2999**

Außengewinde R (Zoll)	Innengewinde Rp (Zoll)	Rohrinnenweite DN (mm)	Außendurchmesser OD (mm)	Kernloch- durchmesser (mm)	Gänge/Inch	Gewindesteigung (mm)
R 1/8	Rp 1/8	6	9,728	8,566	28	0,907
R 1/4	Rp 1/4	8	13,157	11,445	19	0,907
R 3/8	Rp 3/8	10	16,662	14,950	19	1,337
R 1/2	Rp 1/2	15	20,955	18,631	14	1,337
R 3/4	Rp 3/4	20	26,441	24,117	14	1,337
R 1	Rp 1	25	33,249	30,291	11	1,814
R 1 1/4	Rp 1 1/4	32	41,910	38,952	11	1,814
R 1 1/2	Rp 1 1/2	40	47,803	44,845	11	2,309
R 2	Rp 2	50	59,614	56,656	11	2,309
R 2 1/2	Rp 2 1/2	65	75,184	72,226	11	2,309
R 3	Rp 3	80	87,884	84,926	11	2,309
R 4	Rp 4	100	113,030	110,072	11	2,309
R 5	Rp 5	125	138,430	135,472	11	2,309
R 6	Rp 6	150	163,830	160,872	11	2,309